



TECHNICAL DATA SHEET

SAFETAP STICK

Environmentally-Safe Solid Stick Lubricant for Metalworking

DESCRIPTION

SafeTap Stick is a natural-based solid lubricant in stick form that can be used in a wide range of metalworking applications. It is manufactured using renewable raw materials and is environmentally-safe and non-toxic. This natural lubricant eliminates heat build-up and belt loading; apply it before start-up in short-run machining for trouble-free lubrication. SafeTap Stick leaves no waxy residue and cleans off easily with soap and water.

APPLICATIONS

Short-run machining
Belt, disc, and wheel grinding
All metal cutting applications that require extra lubrication

MATERIALS COMPATIBILITY

Recommended for ferrous and nonferrous metals

PHYSICAL PROPERTIES

Appearance.....Light blue solid stick
Specific Gravity0.86
Flash Point.....> 200°F (93°C)
Boiling Point.....> 400°F (204°C)
Melting Point110-120°F (43-49°C)
Sulfur.....None
Chlorine.....None
Silicones.....None
VOCs.....Nil
Mineral Oil.....0%
Water SolubilityInsoluble

USE

SafeTap Stick comes ready-to-use and should be applied as needed.

AVAILABLE SIZES

2.2 oz. *push-up stick (24/case)*.....71907
13 oz. *stick (24/case)*.....71917

HEALTH AND SAFETY

Use proper safety equipment. Avoid contact with skin, eyes, and clothes. Avoid inhaling vapor or mist. Keep away from extreme heat. Keep container closed when not in use. For complete Health and Safety information refer to product Material Safety Data Sheet (MSDS). Product MSDS can be downloaded from www.rocolnorthamerica.com/msds.htm.

For more information contact 800-452-5823 x2 or visit www.rocolnorthamerica.com.

The information in this document is believed to be accurate at the date of issue. Because conditions of use are beyond manufacturer's control no guarantee or warranty is expressed or implied.